



MAPPING MATTERS

YOUR QUESTIONS ANSWERED

The layman's perspective on technical theory and practical applications of mapping and GIS

BY Cassim A. Abdullah, Ph.D., PLS, CP**

QUESTION:

Question: I referenced your highlight article "Harnessing Drones the Photogrammetric Way," which you published in the May 2019 issue of PE&RS, in a conversation about how ground control points (GCPs) are necessary to create accurate maps with unmanned aircraft vehicles (UAVs). I am a licensed surveyor and strongly agree that GCPs are necessary to create accurate maps. My conversational opponent, if you will, insisted that GCPs are not needed if you use an accurate, real-time kinematic (RTK) GPS system on the UAV. Despite your years of research and experience, he is unwilling to accept your assertion. In addition, in the journal article on page 332, you mentioned that at least five GCPs are required for an accurate map. Do you have other data that supports the need for GCPs when mapping with UAVs?

Steve Moran, PLS, Moran Surveying Inc.

Dr. Abdullah: Your colleague is correct if and ONLY if certain conditions are met, and some of these conditions are difficult to meet on a regular basis. These conditions include:

SYSTEM ELECTRONICS

The system electronics and events timing on board the unmanned aircraft system (UAS) and its sensors needs to be aligned to the degree so the shutter mid-exposure pulse (MEP) is determined perfectly. There is always a time offset between the GPS event stamp and the MEP. Some companies invest a great deal in determining this offset, so they can correct for it during the post processing of the GPS tags. They do this because, unless the offset is determined perfectly, the wrong camera position will be measured by the on-board GPS. From my experience, very few UASs on the market time this offset appropriately.

HEALTH OF GPS SIGNAL

The GPS constellation or position dilution of precision (PDOP) supports accurate position determination. This requires flying at a certain time of day and changes according to the project location, date and time. Very few UAS field operations allow us to wait in the field until a better PDOP is met, as you want to spend as little time as you can in the field. A bad GPS signal can cause errors in the camera position. Without the

use of GCPs in the aerial triangulation to model shifts and drifts, you will get positionally inaccurate orthos or digital surface models (DSM). Also, along these lines, the GPS data recording frequency has a noticeable impact on the accuracy of determining the UAS camera position. One hertz (Hz) versus 20 Hz recording frequency can introduce substantial positional errors during an unstable aerodynamic situation. During the 1 Hz GPS recording, the UAS may move 6 to 8 meters between the two epochs. Depending on the flying conditions and the method of interpolation used, estimating the sensor position between two epochs can be challenging and produce inaccuracies. The presence of GCPs in this case can prevent the uncertainty of estimating the image's perspective center position.

"Having GCPs in the aerial triangulation process provides peace of mind. With the proper software, it can be used to model GPS shift and inertial measurement unit (IMU) drift and can flag datum compatibility problems"

GEODETIC DATUM CONVERSION

There is always the possibility of introducing an anomaly in the datum conversion between GPS-based WGS84 and the product's intended vertical datum, such as NAVD88. By not having any GCPs in the project area, you risk introducing errors due to geoid modeling and conversion. Even when flying with airborne GPS for manned aircraft operations, I never advise anyone to execute a project without GCPs and to rely only on airborne GPS. We have always used GCPs in every project; it is an industry standard. Some of the newer UAS operators neither understand nor appreciate that fact. For that reason, industry experts are working hard to help them

Photogrammetric Engineering & Remote Sensing
Vol. 85, No. 10, October 2019, pp. 705–706.
0099-1112/19/705–706

© 2019 American Society for Photogrammetry
and Remote Sensing
doi: 10.14358/PERS.85.10.705

learn the best practices involved in processing data from UAS.

Finally, on this topic, having GCPs in the aerial triangulation process provides peace of mind. With the proper software, it can be used to model GPS shift and inertial measurement unit (IMU) drift and can flag datum compatibility problems. Having GCPs in place also assists with quality control, ensuring you don't blindly deliver products of unknown accuracy.

“There is always the possibility of introducing an anomaly in the datum conversion between GPS-based WGS84 and the product's intended vertical datum, such as NAVD88”

As for the rule I referenced in the journal that requires you to have at least five GCPs in place to create an accurate map, that number is not carved in stone. You can have more or fewer GCPs, based on the project size and shape. This is based on

my research findings and the findings of separate research by Professor Riadh Munjy of California State University, Fresno. Five points safely covers a block of imagery from RTK and non-RTK drones. Four GCPs in the corners results in great horizontal accuracy especially from non-RTK drones. Adding a fifth point in the center of the block is the only way to bring accuracy into the elevation, i.e. Z, in a non-RTK imagery.

***Dr. Abdullah is Chief Scientist and Senior Associate at Woolpert, Inc. He is ASPRS fellow and the recipient of the ASPRS Life Time Achievement Award and the Fairchild Photogrammetric Award.*

The contents of this column reflect the views of the author, who is responsible for the facts and accuracy of the data presented herein. The contents do not necessarily reflect the official views or policies of the American Society for Photogrammetry and Remote Sensing and/or Woolpert, Inc.

Sponsor One Rising Star Today and Make a Difference for Tomorrow

SPONSORSHIP AND MENTORSHIP

ASPRS' Rising Star program is established to advance geospatial science through a sponsorship and mentorship program for early career professional and student members.

SPONSORS

ASPRS Corporations, Regions, Member Groups, and Individual Members are all eligible to sponsor a Rising Star or multiple Rising Stars.

COSTS

- Membership: \$150 annual membership fees for the Rising Star
- Time and Travel Expenses up to \$1000 per year including time and travel for the Rising Star to attend the ASPRS Annual Conference and participate in ASPRS Technical Division activity throughout the year.

BENEFITS

- Listing in *PE&RS* Journals for the entire time of sponsorship to include Sponsor Name and the list of the Rising Star members supported by each sponsor.
- Feature Article – One Rising Star will be featured with a *PE&RS* Highlight Journal Article every three months.

RISING STARS

Be a part of setting the direction of the geospatial profession by contributing your expertise and energy, by guiding industry and professional practice standards, specifications, and by leading, training, and encouraging others to appreciate and apply new mapping and remote sensing technologies.

[HTTP://WWW.ASPRS.ORG/RISING-STAR-PROGRAM](http://www.asprs.org/rising-star-program)

Meet Our Rising Stars!

Chris Stayte

Sponsored by Woolpert, Inc.

Corey Ochsman

Sponsored by Woolpert, Inc.

Collin Hutcheson

Sponsored by Merrick & Company

Charles Krugger

Sponsored by Stahl Sheaffer Engineering, LLC

Kristine Taniguchi-Quan, Ph. D.

Sponsored by Pacific Southwest Region of ASPRS

